

PRODUCT DESCRIPTION

MAVERICK MAVPATCH is a two-component, 100% solids polyurea crack filler. This fast-curing formula allows for quick concrete repair to cracks, joints, holes and other damaged concrete surfaces.

Maverick MavPatch has a low viscosity formula that provides excellent adhesion to concrete, creating a permanent repair to damaged concrete surfaces. **MavPatch** fast cure time allows repaired areas to be opened to traffic in as little as 10 minutes.

FEATURES AND BENEFITS

- Fast Return-to-Service
- Odor Free
- Solvent-Free Formula
- Can Be Applied in Temperatures as Low as 0°F (-18°C)
- Easy 1 to 1 Mix Ratio
- Zero VOC, 100% Solids
- Excellent Adhesion to Concrete
- Impact Resistant
- Pourable

RECOMMENDED USES

- Rebuild joint sidewalls
- High traffic area spalls & crack repairs
- Quick repair in busy areas
- Floor repair & reconditioning
- Fill small concrete defects before coating
- Used to "knit" cracked slabs
- Repair concrete to prevent further damage

PRODUCT INFORMATION

Size	Color/ Finish	Item Number
1 Gal (3.79 L) Complete Kit	Concrete Gray	40002862

TECHNICAL DATA

PHYSICAL DATA	
Components	2 (ISO & Polyol)
Color	Concrete Gray
Solids Content	100%
Mix Ratio (by volume)	1: 1
Gel Time 100 Gram mass @ 72°F (22°C)	20%
VOC (EPA Method 24)	0 g/L

CURE TIMES @ 72F (22C)	
Tack Free	5 minutes
Light Foot Traffic	10 minutes
Heavy Traffic	30 minutes

PHYSICAL PERFORMANCE PROPERTIES

PHYSICAL PROPERTIES	TEST METHOD	RESULTS
Adhesion to Concrete	ASTM D4541	275 psi (1.9 MPa)
Compressive Strength	ASTM C109	5,600 psi
Elongation	ASTM D412	5%
Shore D Hardness	ASTM D2240	74 - 76 D
Tensile Strength	ASTM D412	5,600 psi

SURFACE PREPARATION

Concrete must be sound, clean, dry and free of contaminants such as dirt, dust, grease, oil, silicones and other contaminants that may negatively affect adhesion. Concrete should be a minimum of 28 days old.

For repair of spalled concrete or pop-outs, use a wire brush or twisted wire wheel to remove any loose or deteriorated concrete before application. Cracks must be chased and cleaned with a diamond crack chasing blade on a handheld grinder.

After preparing area, remove all dust and debris with a vacuum. All surfaces must be clean and dry before filling with **MavPatch**.

SAFETY AND TECHNICAL

Refer to the SDS sheet before use. Safety precautions must be strictly followed during storage, handling, and use. Personal protective equipment (PPE) should be worn at all times. PPE will include (but is not limited to): Safety glasses with side shields and high quality nitrile gloves. To acquire additional information or technical and safety data, please visit: www.Maverick.com

TEMPERATURE

Air	0° - 95°F	- 18° - 35°C
Surface	0° - 95°F	- 18° - 35°C
Material	0° - 95°F	- 18° - 35°C

Higher temperatures will shorten pot-life and working time.

APPLICATION EQUIPMENT

Assemble all equipment. Equipment will include (but is not limited to)

- Drill and Jiffy® type mixing blade / stir stick.
- Trowel/wide putty knife if sand is added.
- Painter's tape, duct tape, roller pans, measuring and mixing containers.

APPLICATION PROCEDURE

Maverick MavPatch has a mix ratio of 1 part Base to 1 part Activator by volume.

1. Mix or shake both components separately before use.
2. Premeasure equal amounts of Base and Activator before mixing together.
3. Mix Base and Activator by stir stick or drill mix for 20-30 seconds. Only mix enough material that can be used within 2 to 3 minutes after mixing.

⚠ Do not thin product with any solvents.

Silica sand can be added to form a paste to reduce sag/flow where edge work is needed. Do not add more sand than the volume that will equal the mixed liquids. Be sure silica sand is dry and doesn't contain any moisture before mixing with MavPatch. For best application and usage, premeasure Base, Activator and silica before mixing. Add silica to the Base and premix to ensure equal consistency and maximize the work time. Add Activator to the base and silica mixture and mix for an additional 20-30 seconds.

The finish has a very short work time. Do not over work the material or attempt to rework previously applied finish in order to avoid application defects.



MAVPATCH

CLEAN UP AND DISPOSAL

Clean up mixing and application equipment immediately after use. Use acetone or xylene; do not use alcohol. Follow solvent manufacturer's safety instructions. Be sure to follow all local, state and federal regulations when disposing of materials.

MAINTENANCE

To maintain the appearance and extend the life of the newly sealed surface, it is imperative to have a routine maintenance program. Dirt and debris that is tracked over a finished floor will quickly scratch and dull the surface. Place walk-off mats at entrances. Sweep and mop/scrub floors regularly using soft bristles/pads and a mild cleaner. Some cleaning products and equipment or improper use of these can damage a surface. Remove spills quickly to minimize damage and/or stains. For systems that support parked vehicles or other heavy items on rubber wheels, place a small piece of nonporous material, such as sheet metal or plexiglass between the tires and floor to prevent tire marks. Reapplication may be necessary in heavy traffic areas.

LIMITATIONS

- ⚠ Do not apply outside of the recommended temperature and humidity range.
- ⚠ Do not delay in mixing and pouring mixed material onto the floor.
- ⚠ Do not apply over loose or unsound concrete, asphalt or bitumen substrates, glazed tile or nonporous brick and tile, magnesite, copper, metal, polyesters, or elastomeric membranes.
- ⚠ Do not use as a joint filler substitute.

SHELF LIFE AND STORAGE

12 months from date of manufacture when stored indoors in the original unopened container at 60°F – 85°F (16°C – 29°C) in a dry location with humidity below 65%

- ⚠ Do not allow materials to freeze.

TECHNICAL ASSISTANCE

- ❓ Information is available by calling Maverick
313-889-2526

LIMITED WARRANTY

Maverick warrants this product to be free from defect in the material that affects its performance for a period of one year (from date of purchase). Maverick will replace at no charge the quantity of the Coating that Maverick determines has failed to perform, as the sole and exclusive remedy for any breach of this warranty and/or any other defect or failure of the coating. Proof of purchase is required. Cost of labor for application of any product specifically is excluded. Warranty is nontransferable



CORPORATE OFFICE:
Maverick Performance Solutions
23460 Industrial Park Dr,
Farmington Hills, MI 48335
313-889-2526

PRODUCT DATA SHEET: 02/13/2026

Disclaimer: All information provided by Maverick, Inc. concerning Maverick products, including but not limited to, any recommendations and advice relating to the application and use of Maverick products, is given in good faith based on Maverick's current experience and knowledge of its products when properly stored, handled, and applied under normal conditions in accordance with Maverick's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual conditions and other factors outside of Maverick's control are such that Maverick assumes no liability for the provision of such information, advice, recommendations or instructions related to its products. The uses of Maverick product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s).

Maverick reserves the right to change the properties of its products without notice. All Maverick product(s) are subject to its current terms and conditions of sale which are available by calling (866) 515-8775.